

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Coatings and paints, thinners, paint removers.

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

+353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity — repeated exposure	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label Elements

Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)



Signal word DANGER

Hazard statements

H336 - May cause drowsiness or dizziness

H372 - Causes damage to organs through prolonged or repeated exposure

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

H411 - Toxic to aquatic life with long lasting effects

H226 - Flammable liquid and vapour

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe vapour

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P312 - Call a POISON CENTER or doctor if you feel unwell

P391 - Collect spillage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings if supplied to the general public.

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures 3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	>25 - <40	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)		01-2119458049- 33-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Revision date 30-Jan-2020

Revision Number 2.01

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020 Revision Number 2.01

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control

centre immediately.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO2). Alcohol resistant foam.

Unsuitable extinguishing media Do not use straight streams. CAUTION: Use of water spray when fighting fire may be

inefficient. Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Revision date 30-Jan-2020

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static

Revision date 30-Jan-2020

Revision Number 2.01

discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Supercedes Date: 29-Jan-2020

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Dyke far ahead of spill; use dry sand to contain the flow of material. Absorb with earth,

sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled

containers. Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing

vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient

ventilation, wear suitable respiratory equipment.

General hygiene considerations Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when

using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the

particular national regulations. Keep from freezing.

7.3. Specific end use(s)

Specific Use(s)

Coatings and paints, thinners, paint removers.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies

Chemical name	European Union	Ireland	United Kingdom
Asphalt	=	TWA: 0.5 mg/m ³	TWA: 5 mg/m ³
8052-42-4		STEL: 10 mg/m ³	STEL: 10 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Туре	worker Long term Systemic health effects		
Exposure route	Inhalation		
Derived No Effect Level (DNEL)	330 mg/m ³		

Туре	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	44 mg/kg bw/d

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Туре	Consumer Long term Systemic health effects		
Exposure route	Inhalation		
Derived No Effect Level (DNEL)	71 mg/m³		

Туре	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	26 mg/kg bw/d

Туре	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	26 mg/kg bw/d

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material

and the thickness as well as the temperature. Recommended Use:. Polyvinyl chloride

(PVC).

Skin and body protection Gloves made of plastic or rubber. Antistatic footwear. Wear fire/flame resistant/retardant

clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or

aerosol exposure wear suitable personal respiratory protection and protective suit.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water. Local authorities

should be advised if significant spillages cannot be contained. Prevent product from

Revision date 30-Jan-2020

Revision Number 2.01

entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** viscous Liquid Colour Black Odour Characteristic

Odour threshold No information available

Property Values Remarks • Method

No data available рΗ Melting point / freezing point No data available >= 153 °C Boiling point / boiling range > 39 °C Flash point **Evaporation rate** No data available

Not applicable for liquids . Flammability (solid, gas)

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available kPa

No data available Vapour density Relative density No data available Water solubility Insoluble in water Solubility(ies) No data available Partition coefficient No data available

Autoignition temperature 200 °C

Decomposition temperature No data available Kinematic viscosity $> 370 \text{ mm}^2/\text{s}$

@ 40°C

Dynamic viscosity No data available **Explosive properties** No data available Oxidising properties No data available

9.2. Other information

Solid content (%) No information available **Softening Point** No information available No information available Molecular weight

 $\leq 330 \text{ g/L}$ **VOC Content (%)**

No information available **Density Bulk density** No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available. Reactivity

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical None.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep from freezing.

10.5. Incompatible materials

Incompatible materials Oxidising agent.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause drowsiness or dizziness.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12,	LD50 >15000 mg/Kg (Rattus)	LD50 > 3400 mg/kg (Rattus)	LC50 (4hrs) >13.1 mg/l
n-alkanes, isoalkanes, cyclics,	OECD 401	OECD 402	(Rattus)
aromatics (2-25%)			·
RR-91855-8			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		Micro-organisms			(long-term)
Hydrocarbons, C9-C12,	EL50 (72h) =	10-30 mg/l	-	10-30mg/l		
n-alkanes, isoalkanes,	4.1 mg/l ((daphnia		
cyclics, aromatics	Pseudokirchner			magna)		
(2-25%)	ella subcapitata)					
RR-91855-8	OECD 401					

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or

vPvB.

12.6. Other adverse effects

Other adverse effects No information available.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020 **Revision Number** 2.01

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local

regulations. Dispose of waste in accordance with environmental legislation.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of Contaminated packaging

weld containers.

European Waste Catalogue 17 03 02 bituminous mixtures other than those mentioned in 17 03 01

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Revision date 30-Jan-2020

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to Note:

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Keep from freezing.

Land transport (ADR/RID)

14.1 UN Number UN1999

14.2 Proper Shipping Name Tars, liquid, Environmentally Hazardous

14.3 Transport hazard class(es) 3 Labels 14.4 Packing Group Ш

Description UN1999, Tars, liquid, 3, III, (D/E), Environmentally Hazardous

14.5 Environmental hazards Yes 14.6 Special Provisions None **Classification Code** F1 (D/E) **Tunnel restriction code** Limited Quantity (LQ) 5 L **ADR Hazard Id (Kemmler** 30

Number)

IMDG

14.1 UN number UN1999

14.2 Proper Shipping Name Tars, liquid (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)),

Marine Pollutant

14.3 Transport hazard class(es) 14.4 Packing group Ш

Description UN1999, Tars, liquid (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics

(2-25%)), 3, III, (39°C c.c.), Marine Pollutant

14.5 Marine Pollutant Р 14.6 Special Provisions 955 Limited Quantity (LQ) 5 L F-E, S-E EmS-No.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number UN1999 14.2 Proper Shipping Name Tars, liquid

14.3 Transport hazard class(es) 3 14.4 Packing group

UN1999, Tars, liquid, 3, III Description

14.5 Environmental hazards Yes 14.6 Special Provisions А3

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

Limited Quantity (LQ) 10 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H336 - May cause drowsiness or dizziness

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020 Revision Number 2.01

H372 - Causes damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 30-Jan-2020

Indication of changes

Revision note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Revision date 30-Jan-2020