

SAFETY DATA SHEET

STP® Engine Degreaser Professional

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Engine Degreaser Professional

Product number 73500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine cleaner.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd

Sword House Totteridge Road High Wycombe HP13 6DG

UK

Tel: +44 845 602 1995 euregulatory@energizer.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234

Monday - Thursday: 0830 - 1700

Friday: 0830 - 1530

National emergency telephone Product information has been submitted to the UK National Poisons Information Service

number (NPIS) and is accessible to medical health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Aerosol 1 - H222, H229

Health hazards STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Not Classified

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up.

When sprayed on a naked flame or any incandescent material the aerosol vapours can be

ignited.

2.2. Label elements

Hazard pictograms





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated. H336 May cause drowsiness or dizziness.

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/ spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, xylene

Detergent labelling ≥ 30% aliphatic hydrocarbons, < 5% aromatic hydrocarbons

Supplementary precautionary

statements

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%

aromatics

CAS number: — EC number: 919-857-5

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304

Hydrocarbons, C3-4-rich, petroleum distillate

25 - <50%

50 - 100%

CAS number: 68512-91-4 EC number: 270-990-9

Contains <0.1% w/w 1,3-butadiene (CAS: 106-99-0).

Classification

Flam. Gas 1A - H220 Press. Gas (Liq.) - H280

STP® Engine Degreaser Professional

xylene 2.5 - <5%

CAS number: 1330-20-7 EC number: 215-535-7

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at

rest in a position comfortable for breathing. Keep affected person under observation. Get

medical attention if any discomfort continues.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Do not use

organic solvents. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with the following media: Dry chemicals, sand, dolomite etc. Carbon dioxide (CO2).

Water spray, fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed.

STP® Engine Degreaser Professional

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's

clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all

ignition sources if safe to do so. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections

See Section 11 for additional information on health hazards. For waste disposal, see Section

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, sparks and open flame. Provide adequate ventilation.

Advice on general occupational hygiene

Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take

precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C3-4-rich, petroleum distillate

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Sk, BMGV

ethylbenzene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³ Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin. BMGV = Biological monitoring guidance value.

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and

lighting equipment.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles

or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Do not smoke in work area. Wash promptly with soap and water if skin becomes

contaminated. Wash at the end of each work shift and before eating, smoking and using the

toilet.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective

equipment is suitable for its intended use and is 'UKCA'-marked.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Characteristic.

Odour threshold Not determined.

pH Not determined.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point Not determined.

Evaporation rate Not determined.

Evaporation factor Not determined.

STP® Engine Degreaser Professional

Flammability (solid, gas) Not determined.

Upper/lower flammability or

explosive limits

Relative density

Not determined.

Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Bulk density Not determined.

Solubility(ies) Insoluble in water.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not determined.

Explosive properties Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames

and other sources of ignition. Avoid the accumulation of vapours in low or confined areas.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Decomposition at ambient temperatures may generate the following substances: Carbon dioxide (CO2). Carbon

monoxide (CO). Acrid smoke or fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅o) Based on available data the classification criteria are not met.

STP® Engine Degreaser Professional

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 26,829.27

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 268.29

Skin corrosion/irritation

Animal data

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivoBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways.

Toxicological information on ingredients.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 15,000.0

mg/kg)

Species Rat

Notes (oral LD₅o) REACH dossier information. Read across data.

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,160.0

mg/kg)

STP® Engine Degreaser Professional

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information. Read across data.

ATE dermal (mg/kg) 3,160.0

Skin corrosion/irritation

Animal data Dose: 0.5 ml, ~ 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2).

Oedema score: No oedema (0). REACH dossier information. Read across data. Not

irritating.

Serious eye damage/irritation

Serious eye

Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Read across data. Not

irritating.

Skin sensitisation

damage/irritation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information. Read across data.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Read across data.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Read across data.

Reproductive toxicity

Reproductive toxicity -

fertility

Fertility - NOAEL ≥3000 mg/kg/day, Oral, Rat P REACH dossier information. Read

across data.

Reproductive toxicity - development

Developmental toxicity: - NOAEL: ≥5220 mg/m³, Inhalation, Rat REACH dossier

information.

Hydrocarbons, C3-4-rich, petroleum distillate

Germ cell mutagenicity

Genotoxicity - in vivo

Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity -

fertility

One-generation study - NOAEC 10000 ppm, Inhalation, Rat P REACH dossier

information.

Reproductive toxicity - development

Developmental toxicity: - NOAEC: 10426 ppm, Inhalation, Rat REACH dossier

information.

xylene

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

5,251.0

Species Mouse

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,251.0

Acute toxicity - dermal

Notes (dermal LD₅₀) cATpE: Converted acute toxicity point estimate.

STP® Engine Degreaser Professional

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) cATpE: Converted acute toxicity point estimate.

ATE inhalation (vapours

mg/l)

11.0

Skin corrosion/irritation

Animal data Skin Irrit. 2 - H315 Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 72 hours, Rabbit REACH dossier information. Moderately irritating.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity -

fertility

Two-generation study - NOAEC ≥500 ppm, Inhalation, Rat P, F1 REACH dossier

Developmental toxicity: - NOAEC: ≥500 ppm, Inhalation, Rat REACH dossier

information.

Reproductive toxicity -

information.

development

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated

exposure.

Target organs Central nervous system Kidneys Liver

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Not considered toxic to fish.

Ecological information on ingredients.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

LL₅₀, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) Acute toxicity - fish

REACH dossier information.

Acute toxicity - aquatic

EL₅₀, 24 hours: > 1000 mg/l, Daphnia magna

invertebrates REACH dossier information.

STP® Engine Degreaser Professional

Acute toxicity - aquatic

EL₅₀, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata

plants

REACH dossier information.

Acute toxicity -

EL₅₀, 48 hours: 0.95 mg/l, Tetrahymena pyriformis

microorganisms

QSAR

REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - fish early

NOELR, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

invertebrates

QSAR

REACH dossier information.

Chronic toxicity - aquatic

NOELR, 21 days: 0.23 mg/l, Daphnia magna

QSAR

REACH dossier information.

Hydrocarbons, C3-4-rich, petroleum distillate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 49.47 mg/l, Fish

REACH dossier information.

QSAR

xylene

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 2.6 mg/l, Oncorhynchus mykiss (Rainbow trout)

REACH dossier information.

Read-across data.

Acute toxicity - aquatic

IC₅₀, 24 hours: 1 mg/l, Daphnia magna

invertebrates

REACH dossier information.

Read-across data.

Acute toxicity - aquatic

plants

NOEC, 73 hours: 0.44 mg/l, Pseudokirchneriella subcapitata EC₅o, 73 hours: 2.2 mg/l, Pseudokirchneriella subcapitata

REACH dossier information.

Read-across data.

Acute toxicity -EC₅₀, 24 hours: 96 mg/l, Nitrosomonas

microorganisms REACH dossier information.

Read-across data.

Chronic aquatic toxicity

Chronic toxicity - fish early NOEC, 56 days: > 1.3 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

REACH dossier information.

Chronic toxicity - aquatic

NOEC, 7 days: 1.17 mg/l, Ceriodaphnia dubia

invertebrates

REACH dossier information.

Read-across data.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

STP® Engine Degreaser Professional

Biodegradation Water - Degradation (10%): 5 days

Water - Degradation (50%): 7 days Water - Degradation (61%): 20 days Water - Degradation (80%): 28 days

REACH dossier information.

The substance is readily biodegradable.

Hydrocarbons, C3-4-rich, petroleum distillate

Phototransformation Water - DT₅₀: 1906 days

REACH dossier information.

Calculation method.

Biodegradation Water - Degradation (100%): 385.5 hours

REACH dossier information.

The substance is readily biodegradable.

xylene

Phototransformation Water - DT₅₀ : 1.09 days

REACH dossier information.

Read-across data.

Biodegradation Water - ThOD (68%): 10 days

Water - ThOD (87.8%): 28 days REACH dossier information.

Read-across data.

The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Partition coefficient log Pow: 2.3058 REACH dossier information. QSAR

xylene

Bioaccumulative potential BCF: 5.5 - 12.2, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.

Partition coefficient log Pow: 3.12 REACH dossier information. Read-across data.

12.4. Mobility in soil

Mobility The product is insoluble in water.

Ecological information on ingredients.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Surface tension 24.3 mN/m @ 25°C REACH dossier information.

xylene

Adsorption/desorption

coefficient

Water - log Koc: 2.73 Read-across data. REACH dossier information.

Henry's law constant 623 - 665 Pa m³/mol @ 25°C QSAR REACH dossier information.

Surface tension 28.75 mN/m @ 25°C REACH dossier information. Read-across data.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Do not

puncture or incinerate, even when empty.

Disposal methods Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of the local water authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended). The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use)

(Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

ATE: Acute Toxicity Estimate.

DNEL: Derived No Effect Level.

LC50: Lethal Concentration to 50 % of a test population.

LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to SI 2019 No. 720

Aerosol 1 - H222, H229: Expert judgement. Asp. Tox. 1 - H304, STOT SE 3 - H336:

Calculation method.

Revision comments Section 1: Identification of the substance/mixture and of the company/undertaking // 1.3.

Details of the supplier of the safety data sheet.

Revision date 02/06/2021

Revision 9

Supersedes date 19/03/2020

SDS number 380

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol. H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs (Central nervous system, Kidneys, Liver) through

prolonged or repeated exposure.

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.