



Prestone



## SAFETY DATA SHEET Simoniz Chrome Paint

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Simoniz Chrome Paint

**Product number** SIMP20D

**UFI** UFI: 50NA-N1JD-C00F-6QQ3

**EU REACH registration notes** This is a MIXTURE; no registration information contained in this document. Holts are classed as Downstream User.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Car maintenance product. Paint.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Holt Lloyd Services  
52 Rue des 40 Mines, 60000 – Allonne, France  
Phone: +33 (0)3 64 99 00 32  
info@holtsauto.com

**Contact person** Contact email address: info@holtsauto.com

**Manufacturer** Holt Lloyd International Ltd  
Barton Dock Road  
Stretford  
Manchester  
M32 0YQ - England, UK  
+44 (0) 161 866 4800  
FAX +44 (0) 161 866 4854  
www.holtsauto.com

#### 1.4. Emergency telephone number

**Emergency telephone** UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs

## Simoniz Chrome Paint

**National emergency telephone number** +43 1 31304 5620; chemikalien@umweltbundesamt.at (Austria)  
 +32022649636; info@poisoncentre.be (Belgium)  
 +359 2 9154 409; poison\_centre@mail.orbitel.bg (Bulgaria)  
 +38514686910; toksikologija@hzjz.hr (Croatia)  
 +35722405611; cy-chemregistry@dli.mlsi.gov.cy (Cyprus)  
 +420267082257; biocidy@mzcr.cz (Czech Republic)  
 +45 72 54 40 00; mst@mst.dk (Denmark)  
 +372 794 3500; clp@terviseamet.ee, info@terviseamet.ee (Estonia)  
 +358 5052 000; kirjaamo@tukes.fi (Finland)  
 + 33 3 83 85 21 92; bnpc@chru-nancy.fr (France)  
 +49-30-18412-0; bfr@bfr.bund.de (Germany)  
 +302106479250; +302106479450; devxp.gcs@aade.gr, environment.gcs@aade.gr (Greece)  
 +36 (1) 476 1135; clp.ca@nnk.gov.hu (Hungary)  
 +354 543 22 22; eitur@landspitali.is (Iceland)  
 +353 (1) 809 2166 / +353 (1) 809 2566; chemicalsinfo@beaumont.ie (Ireland)  
 +390649906140; inscweb@iss.it (Italy)  
 +371 67032600; lvgmc@lvgmc.lv (Latvia)  
 +370 70662008; aaa@aaa.am.lt (Lithuania)  
 +320 22649636; +352 24785551; info@poisoncentre.be; direction-sante@ms.etat.lu (Luxembourg)  
 +356 2395 2000; info@mccaa.org.mt (Malta)  
 +31 88 75 585 61; productnotificatie@umcutrecht.nl (The Netherlands)  
 +4573580500; produktregisteret@miljodir.no / +47 21 07 70 00; folkehelseinstituttet@fhi.no (Norway)  
 +48 42 2538 400; biuro@chemikalia.gov.pl (Poland)  
 +351 800 250 250; ciav.tox@inem.pt (Portugal)  
 +40213183606; infotox@insp.gov.ro (Romania)  
 +7 495 621 6885; +7 495 628 1687; rtiac@mail.ru; rtiac2003@yahoo.com (Russia)  
 +421 2 5465 2307; ntic@ntic.sk (Slovakia)  
 + 386 1 522 1293; gp.ukc@kclj.si (Slovenia)  
 +34 917689800; intcf.doc@justicia.es (Spain)  
 +46104566750; giftinformation@gic.se (Sweden)  
 +44 121 507 4123; allistervale@npis.org, sallybradberry@npis.org (UK)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (SI 2019 No. 720)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

#### 2.2. Label elements

##### Hazard pictograms



Signal word

Danger

## Simoniz Chrome Paint

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
<b>UFI</b>	UFI: 50NA-N1JD-C00F-6QQ3
<b>Contains</b>	Hydrocarbons, C9, Aromatics, ACETONE
<b>Supplementary precautionary statements</b>	P273 Avoid release to the environment. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>BUTANE</b>	<b>10-30%</b>
CAS number: 106-97-8	EC number: 203-448-7
<b>Classification</b>	
Flam. Gas 1A - H220	
Press. Gas	
<b>XYLENE</b>	<b>10-30%</b>
CAS number: 1330-20-7	EC number: 215-535-7
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	

## Simoniz Chrome Paint

<b>Hydrocarbons, C9, Aromatics</b>	<b>10-30%</b>
CAS number: 128601-23-0	EC number: 918-668-5
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
<b>ACETONE</b>	<b>10-30%</b>
CAS number: 67-64-1	EC number: 200-662-2
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	
<b>ISOBUTANE</b>	<b>10-30%</b>
CAS number: 75-28-5	EC number: 200-857-2
<b>Classification</b> Flam. Gas 1A - H220 Press. Gas	
<b>Naphtha (petroleum), Light Aromatic</b>	<b>1-5%</b>
CAS number: 64742-95-6	EC number: 918-668-5
<b>Classification</b> Asp. Tox. 1 - H304	

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Not relevant.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Get medical attention promptly if symptoms occur after washing.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea.

## Simoniz Chrome Paint

<b>Ingestion</b>	No harmful effects expected from quantities likely to be ingested by accident.
<b>Skin contact</b>	Causes skin irritation. Prolonged or repeated exposure may cause severe irritation.
<b>Eye contact</b>	Causes serious eye irritation. Prolonged or repeated exposure may cause severe irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Risk of explosion if heated. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	---

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
---	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	For personal protection, see Section 8.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Harmful to aquatic life with long lasting effects. Avoid release to the environment.
----------------------------------	--

### 6.3. Methods and material for containment and cleaning up

<b>Methods for cleaning up</b>	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.
--------------------------------	--

### 6.4. Reference to other sections

<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.
------------------------------------	--

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

<b>Usage precautions</b>	Keep away from heat, sparks and open flame. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Use approved respirator if air contamination is above an acceptable level.
--------------------------	--

### 7.2. Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Do not expose to temperatures exceeding 50°C/122°F.
<b>Storage class</b>	Flammable compressed gas storage. Aerosol containers and lighters

### 7.3. Specific end use(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

## SECTION 8: Exposure controls/Personal protection

## Simoniz Chrome Paint

### 8.1. Control parameters

#### Occupational exposure limits

##### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **ISOBUTANE**

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

#### XYLENE (CAS: 1330-20-7)

##### **DNEL**

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day

Workers - Dermal; Long term systemic effects: 180 mg/kg/day

Consumer - Inhalation; Short term local effects: 174 mg/m<sup>3</sup>

Consumer - Inhalation; Short term systemic effects: 174 mg/m<sup>3</sup>

Workers - Inhalation; Short term systemic effects: 289 mg/m<sup>3</sup>

Workers - Inhalation; Short term local effects: 289 mg/m<sup>3</sup>

Consumer - Inhalation; Long term systemic effects: 14.8 mg/m<sup>3</sup>

Workers - Inhalation; Long term systemic effects: 77 mg/m<sup>3</sup>

#### Hydrocarbons, C9, Aromatics (CAS: 128601-23-0)

##### **DNEL**

Workers - Inhalation; Long term systemic effects: 150 mg/m<sup>3</sup>

Workers - Dermal; Long term systemic effects: 25 mg/kg bw/day

General population - Inhalation; Long term systemic effects: 32 mg/m<sup>3</sup>

General population - Dermal; Long term systemic effects: 56 mg/kg bw/day

General population - Oral; Long term systemic effects: 56 mg/kg bw/day

#### ACETONE (CAS: 67-64-1)

##### **DNEL**

Consumer - Oral; Long term systemic effects: 62 mg/kg/day

Workers - Dermal; Long term systemic effects: 186 mg/kg/day

Consumer - Dermal; Long term systemic effects: 62 mg/kg/day

Workers - Inhalation; Short term local effects: 2420 mg/m<sup>3</sup>

Workers - Inhalation; Long term systemic effects: 1210 mg/m<sup>3</sup>

Consumer - Inhalation; Long term systemic effects: 200 mg/m<sup>3</sup>

## Simoniz Chrome Paint

<b>PNEC</b>	Fresh water; 10.6 mg/l
	marine water; 1.06 mg/l
	Intermittent release; 21 mg/l
	Sediment (Freshwater); 30.4 mg/kg
	Sediment (Marinewater); 3.04 mg/kg
	Soil; 29.5 mg/kg
	STP; 100 mg/l

### Naphtha (petroleum), Light Aromatic (CAS: 64742-95-6)

<b>DNEL</b>	Industry - Dermal; : 25 mg/kg bw/day
	Industry - Inhalation; : 150 mg/m <sup>3</sup>
	Consumer - Dermal; : 11 mg/kg bw/day
	Consumer - Inhalation; : 32 mg/m <sup>3</sup>
	Consumer - Oral; : 11 mg/kg bw/day

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Butyl rubber. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not eat, drink or smoke when using this product. Promptly remove any clothing that becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Silver.
<b>Odour</b>	Acetone. Ketonic.
<b>pH</b>	Not relevant.
<b>Flash point</b>	< 0°C Closed cup.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.7 % Upper flammable/explosive limit: 10.9 %

## Simoniz Chrome Paint

Vapour pressure	3500 hPa @ 20°C
Relative density	0.682 @ 20°C
Solubility(ies)	Immiscible with water.
Auto-ignition temperature	365°C

### 9.2. Other information

<b>Volatile organic compound</b>	This product contains a maximum VOC content of 85.1 %. This product contains a maximum VOC content of 580.4 g/l. UK: (cat B/e): 840 g/l .
----------------------------------	---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
-------------------	---

### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures.
------------------	--

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
---	---

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition.
----------------------------	---

### 10.5. Incompatible materials

<b>Materials to avoid</b>	Strong oxidising agents. Strong acids.
---------------------------	--

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ).
---	---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

<b>Toxicological effects</b>	Information given is based on data of the components and of similar products.
------------------------------	---

#### Acute toxicity - oral

<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
-------------------------------------	--

#### Acute toxicity - dermal

<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
---------------------------------------	--

<b>ATE dermal (mg/kg)</b>	13,198.76
---------------------------	-----------

#### Acute toxicity - inhalation

<b>Notes (inhalation LC<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
---	--

<b>ATE inhalation (vapours mg/l)</b>	72.59
--------------------------------------	-------

#### Skin corrosion/irritation

<b>Skin corrosion/irritation</b>	Causes skin irritation.
----------------------------------	-------------------------

#### Serious eye damage/irritation

<b>Serious eye damage/irritation</b>	Causes serious eye irritation.
--------------------------------------	--------------------------------

#### Respiratory sensitisation



## Simoniz Chrome Paint

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Does not contain any substances known to be toxic to reproduction.

### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Not relevant.

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea.

**Ingestion** May cause discomfort if swallowed.

**Skin contact** Causes skin irritation. Prolonged or repeated exposure may cause severe irritation.

**Eye contact** Causes serious eye irritation. Prolonged or repeated exposure may cause severe irritation.

### Toxicological information on ingredients.

#### BUTANE

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

#### XYLENE

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 3,523.0

**Species** Rat

**ATE oral (mg/kg)** 3,523.0

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.0

## Simoniz Chrome Paint

**Species** Rabbit

**ATE dermal (mg/kg)** 2,000.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 29,000.0

**Species** Rat

**Species** Human

**ATE inhalation (vapours mg/l)** 11.0

**Skin corrosion/irritation**

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Causes serious eye irritation.

**Carcinogenicity**

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

**Aspiration hazard**

**Aspiration hazard** May be fatal if swallowed and enters airways.

### PROPANE

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

**ATE oral (mg/kg)** 5,000.0

### ACETONE

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,800.0

**Species** Rat

**ATE oral (mg/kg)** 5,800.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 7,400.0

**Species** Rabbit

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 76.0

**Species** Rat

## Simoniz Chrome Paint

### Skin corrosion/irritation

**Skin corrosion/irritation** Not irritating.

### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

### Respiratory sensitisation

**Respiratory sensitisation** No information available.

### Skin sensitisation

**Skin sensitisation** Not sensitising.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Negative.

**Genotoxicity - in vivo** Negative.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Reproductive toxicity - fertility** No evidence of reproductive toxicity in animal studies. REACH dossier information.

**Reproductive toxicity - development** No evidence of reproductive toxicity in animal studies.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Central and/or peripheral nervous system damage. Narcotic effects

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Not relevant.

## ISOBUTANE

### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

**ATE oral (mg/kg)** 5,000.0

## Naphtha (petroleum), Light Aromatic

### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 3,492.0

**Species** Rat

### Acute toxicity - dermal

## Simoniz Chrome Paint

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 3,160.0

**Species** Rabbit

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 6,193.0

**Species** Rat

**Skin corrosion/irritation**

**Skin corrosion/irritation** Causes mild skin irritation.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Not irritating

**Respiratory sensitisation**

**Respiratory sensitisation** No information available.

**Skin sensitisation**

**Skin sensitisation** Not sensitising.

**Germ cell mutagenicity**

**Genotoxicity - in vitro** This substance has no evidence of mutagenic properties.

**Carcinogenicity**

**Carcinogenicity** No information available.

**Reproductive toxicity**

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Specific target organ toxicity - single exposure**

**STOT - single exposure** May cause drowsiness or dizziness. May cause respiratory irritation.

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Based on available data the classification criteria are not met.

**Aspiration hazard**

**Aspiration hazard** May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

**Ecological information on ingredients.**

**Naphtha (petroleum), Light Aromatic**

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

**12.1. Toxicity**

**Ecological information on ingredients.**

**XYLENE**

## Simoniz Chrome Paint

### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 13.5 hours: 96 mg/l, Fish
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 7.4 hours: 48 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	IC <sub>50</sub> , 72 hours: 1-10 mg/l, Algae

### ACETONE

### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout) LC <sub>50</sub> , 96 hours: 11000 mg/l, Marinewater fish LC <sub>50</sub> , 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 8800 mg/l, Freshwater invertebrates
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 96 hours: 7200 mg/l, Algae NOEC, 96 hours: 430 mg/l, Algae
<b>Acute toxicity - microorganisms</b>	EC10, NOEC, 30 minutes: 1000 mg/l, Activated sludge
<b>Acute toxicity - terrestrial</b>	LC <sub>50</sub> , 48 hours: 100-1000 µg/cm <sup>2</sup> , Eisenia Fetida (Earthworm)

### Chronic aquatic toxicity

<b>Chronic toxicity - aquatic invertebrates</b>	NOEC, 28 days: 2212 mg/l, Daphnia magna
---	---

### Naphtha (petroleum), Light Aromatic

### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 3.2 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 72 hours: 2.9 mg/l, Algae NOEC, 71 hours: 1 mg/l, Pseudokirchneriella subcapitata
<b>Chronic aquatic toxicity</b>	
<b>Chronic toxicity - fish early life stage</b>	NOEC, 28 days: 1.23 mg/l, Oncorhynchus mykiss (Rainbow trout)
<b>Chronic toxicity - aquatic invertebrates</b>	NOEC, 21 days: 2.14 mg/l, Daphnia magna

## 12.2. Persistence and degradability

### Ecological information on ingredients.

### XYLENE

<b>Biodegradation</b>	The substance is readily biodegradable.
-----------------------	---

### ACETONE

## Simoniz Chrome Paint

**Persistence and degradability** 90 +/- 2.2%; 28 days Rapidly degradable

**Stability (hydrolysis)** The substance is readily biodegradable.

### Naphtha (petroleum), Light Aromatic

**Biodegradation** Rapidly degradable  
Water - Degradation 78%: 28 days

### 12.3. Bioaccumulative potential

#### Ecological information on ingredients.

### ACETONE

**Bioaccumulative potential** Bioaccumulation is unlikely.

### Naphtha (petroleum), Light Aromatic

**Partition coefficient** log Pow: < 4.5

### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### 12.5. Results of PBT and vPvB assessment

#### Ecological information on ingredients.

### ACETONE

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current UK criteria.

### Naphtha (petroleum), Light Aromatic

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current UK criteria.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal methods** Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## SECTION 14: Transport information

**General** As supplied, this product is consigned under the Limited Quantities provisions.

### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

## Simoniz Chrome Paint

UN No. (ADN) 1950

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Authorisations (SI 2020 No. 1577 Annex XIV) No specific authorisations are known for this product.

Restrictions (SI 2020 No. 1577 Annex XVII) No specific restrictions on use are known for this product.

## Simoniz Chrome Paint

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	<p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>BOD: Biochemical Oxygen Demand.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DNEL: Derived No Effect Level.</p> <p>EC<sub>50</sub>: 50% of maximal Effective Concentration.</p> <p>GHS: Globally Harmonized System.</p> <p>IARC: International Agency for Research on Cancer.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>LC50: Lethal Concentration to 50 % of a test population.</p> <p>LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>LOAEC: Lowest Observed Adverse Effect Concentration.</p> <p>LOAEL: Lowest Observed Adverse Effect Level.</p> <p>LOEC: Lowest Observed Effect Concentration.</p> <p>NOAEC: No Observed Adverse Effect Concentration.</p> <p>NOAEL: No Observed Adverse Effect Level.</p> <p>NOEC: No Observed Effect Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>PNEC: Predicted No Effect Concentration.</p> <p>REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>SVHC: Substances of Very High Concern.</p> <p>UVCB - Unknown or variable composition, complex reaction products or Biological materials.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
<b>Classification procedures according to SI 2019 No. 720</b>	<p>Aerosol 1 - H222, H229: Calculation method. Skin Irrit. 2 - H315: Calculation method. Eye Irrit. 2 - H319: Calculation method. STOT SE 3 - H336: Calculation method. Aquatic Chronic 3 - H412: Calculation method.</p>
<b>Issued by</b>	Regulatory Specialist
<b>Revision date</b>	25/02/2022
<b>Revision</b>	5
<b>Supersedes date</b>	16/07/2021
<b>SDS number</b>	15037



## Simoniz Chrome Paint

### Hazard statements in full

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.