



Prestone



SAFETY DATA SHEET Simoniz Zinc Primer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Simoniz Zinc Primer

Product number SIMP10D

UFI UFI: F5QV-C2S0-J67C-8NHK

EU REACH registration notes This is a MIXTURE; no registration information contained in this document. Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint. Primer.

1.3. Details of the supplier of the safety data sheet

Supplier Holt Lloyd International Ltd
Barton Dock Road
Stretford
Manchester
M32 0YQ - England, UK
+44 (0) 161 866 4800
FAX +44 (0) 161 866 4854
www.holtsauto.com

Contact person Contact email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs

National emergency telephone number National Poisons Information Service
City Hospital, Birmingham B187QH, United Kingdom
Telephone: +44 121 507 4123
Email: allistervale@npis.org, sallybradberry@npis.org

www.npis.org

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

2.2. Label elements

Simoniz Zinc Primer

Hazard pictograms



Signal word

Danger

Hazard statements

EUH208 Contains Fatty acids, tall-oil, compounds with oleylamine. May produce an allergic reaction.
 H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with local regulations.

UFI

UFI: F5QV-C2S0-J67C-8NHK

Contains

ACETONE, Naphtha (petroleum), Light Aromatic

Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P391 Collect spillage.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIMETHYL ETHER	25-50%
CAS number: 115-10-6	EC number: 204-065-8
Classification	
Flam. Gas 1A - H220	
Press. Gas (Liq.) - H280	

Simoniz Zinc Primer

ZINC POWDER - ZINC DUST (STABILISED)	25-50%
CAS number: 7440-66-6	EC number: 231-175-3
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
Hydrocarbons, C9, aromatics	10-25%
CAS number: 128601-23-0	EC number: 918-668-5
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H335, H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
ACETONE	10-25%
CAS number: 67-64-1	EC number: 200-662-2
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
XYLENE	5-10%
CAS number: 1330-20-7	EC number: 215-535-7
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
ZINC OXIDE	1-5%
CAS number: 1314-13-2	EC number: 215-222-5
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
Fatty acids, tall-oil, compounds with oleylamine	<1%
CAS number: 85711-55-3	EC number: 288-315-1
Classification	
Skin Sens. 1 - H317	

Simoniz Zinc Primer

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Treat symptomatically.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Simoniz Zinc Primer

Storage precautions Keep container tightly closed, in a cool, well ventilated place.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

DIMETHYL ETHER (CAS: 115-10-6)

DNEL	Workers - Inhalation; Long term systemic effects: 1894 mg/m ³ Workers - Hazard for the eyes no hazard identified General population - Inhalation; Long term systemic effects: 471 mg/m ³ General Population - Hazard for the eyes no hazard identified
PNEC	Fresh water; 0.155 mg/l marine water; 0.016 mg/l STP; 160 mg/l Sediment (Freshwater); 0.681 mg/kg sediment dry weight Sediment (Marinewater); 0.069 mg/kg sediment dry weight Soil; 0.045 mg/kg soil dry weight

ACETONE (CAS: 67-64-1)

DNEL	Consumer - Oral; Long term systemic effects: 62 mg/kg/day Workers - Dermal; Long term systemic effects: 186 mg/kg/day Consumer - Dermal; Long term systemic effects: 62 mg/kg/day Workers - Inhalation; Short term local effects: 2420 mg/m ³ Workers - Inhalation; Long term systemic effects: 1210 mg/m ³ Consumer - Inhalation; Long term systemic effects: 200 mg/m ³
-------------	---

Simoniz Zinc Primer

PNEC	Fresh water; 10.6 mg/l
	marine water; 1.06 mg/l
	Intermittent release; 21 mg/l
	Sediment (Freshwater); 30.4 mg/kg
	Sediment (Marinewater); 3.04 mg/kg
	Soil; 29.5 mg/kg
	STP; 100 mg/l

Hydrocarbons, C9, aromatics (CAS: 128601-23-0)

DNEL	Industry - Dermal; : 25 mg/kg bw/day
	Industry - Inhalation; : 150 mg/m ³
	Consumer - Dermal; : 11 mg/kg bw/day
	Consumer - Inhalation; : 32 mg/m ³
	Consumer - Oral; : 11 mg/kg bw/day

XYLENE (CAS: 1330-20-7)

DNEL	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
	Workers - Dermal; Long term systemic effects: 180 mg/kg/day
	Consumer - Inhalation; Short term local effects: 174 mg/m ³
	Consumer - Inhalation; Short term systemic effects: 174 mg/m ³
	Workers - Inhalation; Short term systemic effects: 289 mg/m ³
	Workers - Inhalation; Short term local effects: 289 mg/m ³
	Consumer - Inhalation; Long term systemic effects: 14.8 mg/m ³
	Workers - Inhalation; Long term systemic effects: 77 mg/m ³

8.2. Exposure controls

Protective equipment



Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves are made of the following material: Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not smoke in work area. Do not eat, drink or smoke when using this product.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Grey.
Odour	Acetone.

Simoniz Zinc Primer

Flash point	<0°C
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.1% Upper flammable/explosive limit: 10.9%
Relative density	~0.705 @ °C
Partition coefficient	Not available.
Auto-ignition temperature	200°C
9.2. Other information	
Volatility	83.18
Volatile organic compound	This product contains a maximum VOC content of 596.4 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Flammable/combustible materials.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Flammable/combustible materials.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 22,000.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (gases ppm) 90,000.0

ATE inhalation (vapours mg/l) 220.0

ATE inhalation (dusts/mists mg/l) 30.0

Simoniz Zinc Primer

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not relevant.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin contact

Prolonged and frequent contact may cause redness and irritation.

Eye contact

Causes serious eye irritation. Repeated exposure may cause chronic eye irritation.

Route of exposure

Inhalation Skin and/or eye contact

SECTION 12: Ecological information

Ecotoxicity

Dangerous for the environment if discharged into watercourses. WGK2

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Simoniz Zinc Primer

Acute toxicity - microorganisms Not available.

Acute toxicity - terrestrial Not available.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not available.

Short term toxicity - embryo and sac fry stages Not available.

Chronic toxicity - aquatic invertebrates Not available.

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

Biological oxygen demand Not available.

Chemical oxygen demand Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

Adsorption/desorption coefficient No information available.

Henry's law constant No information available.

Surface tension No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

Simoniz Zinc Primer

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ICAO packing group None

ADN packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Simoniz Zinc Primer

EU legislation

VOC Directive - 2004/42/EC
Aerosol Dispensers Directive 2008/47/EC (2008/47/EC)

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>BOD: Biochemical Oxygen Demand.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DNEL: Derived No Effect Level.</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>GHS: Globally Harmonized System.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>LC50: Lethal Concentration to 50 % of a test population.</p> <p>LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577.</p> <p>SVHC: Substances of Very High Concern.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Revision date	09/01/2023
Revision	4
Supersedes date	27/01/2020
SDS number	15064
Hazard statements in full	<p>H220 Extremely flammable gas.</p> <p>H222 Extremely flammable aerosol.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H229 Pressurised container: may burst if heated.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H331 Toxic if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>EUH208 Contains Fatty acids, tall-oil, compounds with oleylamine. May produce an allergic reaction.</p>